

PA-172

Features:

- 1Ø/3Ø Power Measurement
- RS-232 Interface
- Jaw Open : 50mm



AC VOLTAGE RMS

Range	Resolution	Accuracy
80V	0.1V	± 1.0% of rdg + 5 digits
180V		
400V	1V	
600V		

AC CURRENT RMS

Range	Resolution	Accuracy
20A	0.01A	± 2.0% of rdg + 5 digits
40A		
100A	0.1A	
200A		
450A	1A	
1000A		

SINGLE-PHASE ACTIVE POWER

Range	Resolution	Accuracy
30kW	0.01kW	± 3 % of rdg + 5 digits
60kW		
120kW	0.1kW	
150kW		
300kW		
600kW		

THREE-PHASE ACTIVE POWER

Range	Resolution	Accuracy
3kVA	0.001kVA	± 3 % of rdg + 5 digits
12kVA	0.01kVA	
30kVA		
120kVA	0.1kVA	
150kVA		
600kVA		

POWER FACTOR

Range	Resolution	Accuracy
0.3 - 1 Capacitive	0.001	± 0.02 % of rdg + 2 digits
0.3 - 1 Inductive		

PASSIVE POWER

Range	Resolution	Accuracy
3kVAr	0.001kVAr	± 3 % of rdg + 5 digits
12kVAr	0.01kVAr	
30kVAr		
120kVAr	0.1kVAr	
150kVAr		
600kVAr		

FREQUENCY

Range	Resolution	Accuracy
30Hz - 1kHz	0.1Hz	± 0.5 % of rdg + 1 digit

POWER AA 1.5V X 4

- Standard Accessories : Test Lead, Soft Carrying Case, USB cable & Software, Manual
- Dimension : 300(H) x 103(W) x 51(D)mm