



FEATURES :

- 3½ DIGIT MANUAL MULTIMETER
- 1,999 COUNT
- AUTO POWER OFF UNDER NATURAL OPERATION
- TERMINAL SHUTTER INTERLOCK MECHANISM
- TRANSISTOR TESTING

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1 mV	±0.5% of rdg ±1 digit
2V	1mV	±0.5% of rdg ±3 digits
20V	10mV	
200V	100mV	±0.8% of rdg ±3 digits
1000V	1V	

DC CURRENT

RANGE	RESOLUTION	ACCURACY
20µA	10nA	±1.2% of rdg±3 digits
2mA	1µA	±1.0% of rdg±3 digits
200mA	100µA	±1.5% of rdg±5 digits
10A	10mA	±2.0% of rdg±10 digits

TEMPERATURE

RANGE	RESOLUTION	ACCURACY
-20~0°C	1°C	±5.0% of rdg±5 digits
0~400°C		±1.0% of rdg±3 digits
400~1000°C		±2.0% of rdg±3 digits

TRANSISTOR hFE TEST

RANGE	TEST RANGE	TEST CURRENT/VOLTAGE
NPN or PNP	0-1000	1b=10µF/VCE=3A

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
2V	1mV	±1.0% of rdg ±5 digits
20V	10mV	
200V	100mV	±1.2% of rdg ±5 digits
700V	1V	

AC CURRENT

RANGE	RESOLUTION	ACCURACY
20mA	10µA	±1.2% of rdg±5 digits
200mA	100µA	±2.0% of rdg±5 digits
10A	10mA	±3.0% of rdg±10 digits

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±1.0% of rdg±10 digits
2kΩ	1Ω	±1.0% of rdg±1 digits
20kΩ	10Ω	
200kΩ	100Ω	±1.0% of rdg±5 digits
20MΩ	10kΩ	
200MΩ	100kΩ	±5.0% of rdg-10 digits±20 digits

CAPACITANCE

RANGE	RESOLUTION	ACCURACY
2nF	1pF	±4.0% of rdg±3 digits
200nF	0.1nF	
2µF	1nF	±5.0% of rdg±3 digits
200µF	100nF	

FREQUENCY

RANGE	RESOLUTION	ACCURACY
200KHz	100Hz	±1.5% of rdg±10 digits

POWER : 9V (6F22) X 1

Dimension	: H191 x W82 x D36 mm
Weight	: Approx. 310 Gms.
Accessories	: Test leads, Fuse, Manual TP04 Thermocouple & Battery.
Qty	: 42 Pcs. in a Box.