



FEATURES :

- K TYPE PROBE INTERFACE
- FAST & EASY MEASUREMENT
- °C OR °F SELECTION
- TRIGGER LOCK
- ADJUSTABLE EMISSIVITY : 0.1-1.0
- MAX, MIN, DIF, AVG RECORD
- REC DATALOGGER FUNCTION FOR 12 POINTS
- LCD DISPLAY WITH BACKLIGHT
- TRIGGER LOCK
- ADJUSTABLE HIGH / LOW ALARM
- AUTOMATIC RANGE SELECTION
- AUTOMATIC DATA HOLD FUNCTION
- PRECISE IR AND TK TEMPERATURE MEASUREMENT
- BUILT-IN ROUND LASER POINTER INCREASE THE TARGET ACCURACY



Back light



Temp



Low Battery Indication

TECHNICAL DATA :

RANGE	IR	-50°C~1250°C / -58°F~2282°F
	TK	-50°C~1370°C / -58°F~2498°F
ACCURACY	IR : -50°C~0°C/-58°F~32°F ±4°C/7.2°F IR : 0°C~500°/32°F~932°F ±1.5%±2°C/3.6°F ABOVE 500°C~932°F :±2.0% ±2°C/3.6°F TK : -50°C~1370°/-58°F~2498°F : ±1.5%±1°C/1.8°F	
RESOLUTION	0.1°C(0.1°F) <1000, 1°C(1°F)>1000	
DISTANCE SPORT RATIO	30:1	
EMISSIVITY	ADJUSTABLE : 0.10~1.0	
RESPONSE TIME	<250ms	
SPECTRAL RESPONSE	8~14um	
OVER RANGE INDICATION	LO	HI
POLARITY DISPLAY	Auto Display "-" indicates negative, while positive with no sign	
DIODE LASER	OUTPUT <1mW/630-670nm Level 2(II) Laser	
AUTO POWER OFF	AUTOMATICALLY AFTER 35 SECOND	
RELATIVE HUMIDITY	OPERATING : 10 TO 95% RH	

POWER : 9V (6F22) x 1

Dimension	: H192 x W95 x D83 mm
Weight	: Approx. 275 Gms.
Accessories	: Soft Carry Case, Type K Probe, Hook, User Manual & Battery
Qty	: 40 Pcs. in a Box.